

**Absolute protection,
outdoor** ZERO DECK, eco-friendly
high performance water-oil for outdoor use



ZERO
concept



VERMEISTER
SOLUTIONS FOR WOOD FLOORS

ZERO DECK Eco-friendly high performance water-oil specifically designed for outdoor use.


Outdoor decks are the most complicated to be protected from exposure to weather conditions such as rain, frost, sun and varying temperatures. Vermeister is now proposing a system of complete protection: ZERO DECK. The special combination of water and oil has led us to get amazing performance in terms of resistance to grant your outdoor wood floor total protection, while respecting the environment.

Low environmental impact

Particular consideration must be given to the healthiness of the air when choosing chemical products to be used for installing wood floors indoors. Those wishing to achieve the maximum level of protection for the health, environmental cleanliness and quality of the indoor air must refer to the EMICODE EC1 PLUS® quality mark. The products classified as “very low emission” and bearing the GEV EMICODE EC1 PLUS® mark, offer the best guarantee against indoor air pollution and a very high level of protection for the health and environmental compatibility. Although ZERO DECK has a negligible VOC value, it is a product for outdoor use and therefore cannot provide for the EC1 classification EC1

In the human health and environment respect ZERO DECK features itself for the following aspects:

- Free from hardeners agents based on heavy metals
- NMP-free
- NO hazard label
- Formulated with renewable raw materials



Quick facts

Low environmental impact
High protection against UV rays
Prevents greying maintaining the long lasting colour of the wood
Excellent water repellency
More filling power compared to a traditional oil
Excellent toning effect
Ideal for flooring and wood products both indoors and out

Technical data

Method of application	Roller, brush, applicator
Average coverage per coat (gr./sqm.)	70/100
Dry for eventual 2 nd coat (hours)	After 6, within 24
Standard size (lt)	5



Maintenance

The routine maintenance of a floor protected with ZERO DECK consists of three phases:

- dusting with a soft broom or vacuum cleaner;
- washing with SOAP OIL
- application of DECK CARE

According to the exposure of the floor (between 3 and 6 months approximately) apply a coat of ZERO DECK.

Maintenance with ZERO DECK does not require sanding beforehand.

