


# ZERO%

There is only ONE ORIGINAL and many pale imitations



In 2006 we formulated **THE FIRST TWO-COMPONENT SOLVENT-FREE ADHESIVE: ZERO %**. The experience acquired over the years is our guarantee of the reliability of the most widely sold product of its type: **more than 9,000,000 kg of the product have been sold since 2006.**

**THE ABSENCE OF SOLVENTS** and the very low emission of volatile organic substances, both during application and when the floor is in use, is certified by the **EC1 CLASSIFICATION.**



Being certified EMICODE EC1, ZERO% may apply for the awarding of the EQ credit for Indoor Environmental Quality - Low-Emitting Materials of the new international certification standard LEED v4.

# ZERO%, the original.

## The first two-component SOLVENT-FREE adhesive

In 2006, Vermeister was the first company to believe in, formulate and introduce onto the wood floor market a two component SOLVENT-FREE adhesive made with environmentally-friendly materials. Zero% is the result of the continual research and innovation performed by the Vermeister laboratories in order to reduce the environmental impact and today it is the most widely used solvent-free adhesive. Exceptional coverage and stable ridge.

✓ The launch of the ZERO% adhesive

2006

✓ Vermeister, the FIRST company to have formulated a two-component solvent-free adhesive

1

✓ Our guarantee, the number of kg sold up until now

9.000.000


✓ Kg per cm<sup>2</sup> of tensile strength

70

✓ Content of solvent

0

✓ The very low emission of volatile organic substances, both during application and when the floor is in use, is certified by the EC1 classification.



### TECHNICAL DATA

#### chemical – physical characteristics at 20°C

Catalysis ratio A:B (weight)	9:1
Pot-life (hours)	2
Open time (hours)	1
Tensile strength (UNI EN 14293 N/mm <sup>2</sup> )	> 6,0
Elasticity (mm)	>1,4
Pull off (Kg/cm <sup>2</sup> )	> 70
Ready for traffic (hours)	24/48
Interval before sanding (days)	3
Average coverage (g/m <sup>2</sup> )	900/1400

