

**DESCRIPTION**

Mixture of high quality solvents for thinning single component polyurethane primers and for the preparation of solvent based fillers.

TECHNICAL DATA CHEMICAL-PHYSICAL CHARACTERISTICS at 20°C (indicative values not constituting product specifications):

Standard packaging (Lt)

10

10 Lt

APPLICATION

DILUENTE EXTRA is recommended for thinning PRIMER UR 50, according to the instructions given in the relevant technical data sheet. It is also recommended for thinning PRIMER SF to improve the penetration of the first coat into the support. However, if DILUENTE EXTRA is used to thin "solvent-free" primers, their use is subject to the presence of a steam barrier to prevent traces of solvent from penetrating into the rooms below. Furthermore, it is also recommended for thinning binders for the preparation of solvent based fillers (LEGA STUCCO, LEGA STUCCO PLUS) when the binder/wood powder mixture requires improved slide.

NOTES

THE ADDITION OF THIS PRODUCT TO SYSTEMS SUBJECT to EC Dir.2004/42 MAY RAISE THE VOC VALUE BEYOND THE PERMITTED LIMITS: CHECK THE MAXIMUM QUANTITIES ALLOWED.

Safety precautions. Keep the product in a tightly closed, upright container in a cool place away from sources of heat. The product is classified and coded in compliance with EC Directives/regulations concerning hazardous substances. The information for the user is given in the relevant safety sheet. Empty containers or those containing slight traces of the product must be disposed of in accordance with local regulations. VerMeister S.p.A. guarantees that the details given in this sheet are provided to the best of the company's technical-scientific knowledge and experience; however, the company cannot be held responsible in any way for the results obtained with the products as the conditions of application are beyond the company's control. It is always advisable to check the suitability of the product to each specific circumstance. This sheet cancels and replaces all previous editions