



DESCRIPTION

Very fast drying single component sealer for wood floors with nitrocellulose base. The rapid drying time makes the product particularly suitable for fast finishing cycles. FLASH has been formulated to offer maximum performance with regard to pore closure and as a result it is the single component sealer that provides the best uniformity and limits the absorption of subsequent coats of paint. This helps to overcome possible defects due to areas of excessive absorption. THE PRODUCT CAN BE OVERCOATED without sanding even with single component waterborne finishes. Furthermore, it has a considerable water repellent action.

10 Lt

TECHNICAL DATA CHEMICAL-PHYSICAL CHARACTERISTICS at 20°C (indicative values not constituting product specifications):	
Completely dry (minutes)	30
Overcoating (minutes)	30
Application method	Roller, Brush
Average coverage per coat (g/m ²)	80/100
Adhesion (checkering)	100%
Stability and storage (in original, unopened containers stored in a cool, dry place) (months)	12
Calculated VOC (g/lit)	750
Max permitted dilution (EC Dir.2004/42)	None
To clean tools	SOLVENTE LAVAGGIO
Standard packaging (Lt)	2x10

APPLICATION

Sand and fill the floor using Vermeister binders for solvent based fillers and then vacuum carefully. Apply one coat of FLASH following the recommended quantities (80/100 g/m²). After about 30 minutes the subsequent coats of finish can be applied without sanding.

NOTES

DO NOT OVERCOAT WITH SINGLE COMPONENT SOLVENT BASED POLYURETHANE FINISHES as these products may have a reaction leading to a strong and uneven yellowing of the floor.

Stir well before use.

Product subject to the restrictions prescribed by EC Dir.2004/42.

Safety precautions. Keep the product in a tightly closed, upright container in a cool place away from sources of heat. The product is classified and coded in compliance with EC Directives/regulations concerning hazardous substances. The information for the user is given in the relevant safety sheet. Empty containers or those containing slight traces of the product must be disposed of in accordance with local regulations. Vermeister S.p.A. guarantees that the details given in this sheet are provided to the best of the company's technical-scientific knowledge and experience; however, the company cannot be held responsible in any way for the results obtained with the products as the conditions of application are beyond the company's control. It is always advisable to check the suitability of the product to each specific circumstance. This sheet cancels and replaces all previous editions