



DESCRIPTION

Single component oil modified urethane finish for wood floors. Thanks to the use of innovative resins, technological additives and special drying agents, this product enables unique abrasion and scratch resistance characteristics to be achieved. As for the application, it is outstanding for the ease of use and for the long open time. OIL PLUS represents a valid alternative to impregnation processes as it offers greater floor protection and does not require any particular maintenance work.

5 Lt



TECHNICAL DATA CHEMICAL-PHYSICAL CHARACTERISTICS at 20°C (indicative values not constituting product specifications):	
Dust dry (hours)	2
Impression dry (hours)	3
Dry for sanding (hours)	24/48
Light Traffic (days)	3/4
Careful Use (days)	5
Completely Dry (days)	10
Degree of gloss OIL PLUS X-MATT (gloss)	10
Degree of gloss OIL PLUS 30 (gloss)	30
Degree of gloss OIL PLUS 60 (gloss)	60
Application method	Roller, Brush
Average coverage per coat (g/m ²)	80/95
Adhesion (checkering) (%)	100
Stability and storage (in original, unopened containers stored in a cool, dry place) (months)	12
Calculated VOC (g/lit)	500
Max permitted dilution (Dir.2004/42/CEE)	None
To clean tools	DILUENTE PLUS
Standard packaging (Lt)	5

APPLICATION

First sand and fill the floor using Vermeister binders for solvent based fillers and then clean carefully. Apply a first coat of pure product, wait 24 hours, sand lightly using a very fine abrasive disc screen and then apply a second coat of OIL PLUS. The floors treated in this way will have a uniform appearance, without defects, similar to wood floors treated with oils and waxes. Alternatively, our COLOR.OIL can be applied as the first coat (except the WHITE and GREY versions) to obtain antique or coloured effects.

MAINTENANCE

The maintenance of finished floors must only be carried out using DETERGENTE NEUTRO and/or IDRONET. Do not use alcohol, ammonia or detergents for hard surfaces. For further information see the MAINTENANCE SHEET.

NOTES

To prevent problems of adhesion from arising, it is advisable not to wait more than 3 days between the application of the various coats. Moreover, rather than use the X-MATT version as the sealer, it is preferable to choose the less opaque versions.

Do not replace any leftover product in the container!

Stir well before use.

Product subject to the restrictions prescribed by EC Dir.2004/42.

DRY FOR SANDING: interval before the floor is ready for sanding

LIGHT TRAFFIC: interval before several people can walk on the floor.

CAREFUL USE: interval before the floor is ready for moderate use.

COMPLETELY DRY: interval before the floor is ready for complete use: e.g. for furniture removal, to allow other craftsmen to carry out work, to start maintenance of the floor, etc.

Safety precautions. ANY RESIDUE PRODUCT COULD SELF-COMBUST and cloths and tools impregnated with the oil must be soaked in water and, before being disposed of, they must be left to dry in the open air, in areas where there are no risks of flames spreading. Keep the product in a tightly closed, upright container in a cool place away from sources of heat. The product is classified and coded in compliance with EC Directives/regulations concerning hazardous substances. The information for the user is given in the relevant safety sheet. Empty containers or those containing slight traces of the product must be disposed of in accordance with local regulations. VerMeister S.p.A. guarantees that the details given in this sheet are provided to the best of the company's technical-scientific knowledge and experience; however, the company cannot be held responsible in any way for the results obtained with the products as the conditions of application are beyond the company's control. It is always advisable to check the suitability of the product to each specific circumstance. This sheet cancels and replaces all previous editions.