



TECHNICAL DATA SHEET

FETLESS

Adhesion improver



5 Lt



1 Lt

DESCRIPTION

A solvent and compound based product for improving the adhesion of two-component adhesives on enamelled or glazed surfaces such as: marble, ceramic and terrazzo tiles, etc. It is also recommended for thinning the primer EPO 2 and Vermeister two-component epoxy-polyurethane adhesives.

TECHNICAL DATA CHEMICAL-PHYSICAL CHARACTERISTICS at 20°C (indicative values not constituting product specifications):

| | |
|---|-------|
| Average coverage per coat (g/m ²) | 30/50 |
| Stability and storage (in original, unopened containers stored in a cool, dry place) (months) | 12 |
| Standard packaging (Lt) | 1-5 |

APPLICATION

Wet a clean, dry cloth with FETLESS and then apply a thin, even layer on the surface to be treated in a quantity of between 30 and 40 g per m². When dry, the wood floor can be laid in the usual way.

NOTES

Product for professional use.

Safety precautions. Keep the product in a tightly closed, upright container in a cool place away from sources of heat. The product is classified and coded in compliance with EC Directives/regulations concerning hazardous substances. The information for the user is given in the relevant safety sheet. Empty containers or those containing slight traces of the product must be disposed of in accordance with local regulations. Vermeister S.p.A. guarantees that the details given in this sheet are provided to the best of the company's technical-scientific knowledge and experience; however, the company cannot be held responsible in any way for the results obtained with the products as the conditions of application are beyond the company's control. It is always advisable to check the suitability of the product to each specific circumstance. This sheet cancels and replaces all previous editions