



TECHNICAL DATA SHEET

PRIMACRIL

Acrylic primer in a watery solution



10 Lt

DESCRIPTION

Product based on acrylic resins in a watery dispersion specially formulated to strengthen flaking or crumbly subfloors.

TECHNICAL DATA CHEMICAL-PHYSICAL CHARACTERISTICS at 20°C (indicative values not constituting product specifications):

Average coverage per coat (g/m ²)	100/250
Stability and storage (in original, unopened containers stored in cool, dry place) (months)	12
Calculated VOC (g/lit)	10
Max permitted dilution (EC Dir.2004/42)	Only water
To clean tools	WATER
Standard packaging (Lt)	10

APPLICATION

STRENGTHENING AND ANTI-DUST TREATMENT

Prepare the surfaces to be treated by removing all traces of material that may act as a separating agent (oils, greases, paints, dust, etc.). PRIMACRIL must be diluted, according to the absorbcency of the subfloor, in the following ratio:

1 part PRIMACRIL and 1 or 2 parts water. Apply this solution with a roller or brush to the amount of 100-250 g/m² . If necessary, apply another coat of product after 2 and within 12 hours. Before proceeding with the subsequent laying phase, wait at least 2-3 days. This interval may be considerably longer according to particular morphological conditions of the screed and environmental factors. Therefore, the degree of moisture in the screed must be checked using a carbide hygrometer before continuing with the gluing. Only use Vermeister vinyl adhesives. If a film forms on the surface, some sand must be scattered on the primer while still fresh. Once the primer has dried, the excess sand must be removed.

ADHESION IMPROVER FOR CEMENT LEVELLING

Prepare the surfaces to be treated by removing all traces of material that may act as a separating agent (oils, greases, paints, dust, etc.). Apply one coat of pure PRIMACRIL and then apply the cement levelling product (with RASOSELF).

NOTES

Do not apply the product below 10°C or above 30°C.

Store above freezing.

Product subject to the restrictions prescribed by EC Dir.2004/42.

Product for professional use.

Safety precautions. Keep the product in a tightly closed, upright container in a cool place away from sources of heat. The product is classified and coded in compliance with EC Directives/regulations concerning hazardous substances. The information for the user is given in the relevant safety sheet. Empty containers or those containing slight traces of the product must be disposed of in accordance with local regulations. VerMeister S.p.A. guarantees that the details given in this sheet are provided to the best of the company's technical-scientific knowledge and experience; however, the company cannot be held responsible in any way for the results obtained with the products as the conditions of application are beyond the company's control. It is always advisable to check the suitability of the product to each specific circumstance. This sheet cancels and replaces all previous editions.