



TECHNICAL DATA SHEET

REVIN LL

Transparent single component vinyl adhesive



10 Kg

DESCRIPTION

Transparent vinyl adhesive in a watery dispersion suitable for gluing the heads of solid wood flooring without interlocking to reduce "sliding" during the laying phases. Compared with traditional vinyl adhesives, this product offers the undoubted advantage of being completely transparent after drying. It is also recommended as a highly resistant adhesive for gluing wood profiles and all wooden materials in general.

TECHNICAL DATA CHEMICAL-PHYSICAL CHARACTERISTICS at 20°C (indicative values not constituting product specifications):

Open time (minutes)	8/12
Stability and storage (in original, unopened containers stored in a cool, dry place) (months)	12
Standard packaging (Kg)	10

NOTES

Do not apply the product below 10°C or above 30°C.
Store above freezing.

Safety precautions. Keep the product in a tightly closed, upright container in a cool place away from sources of heat. The product is classified and coded in compliance with EC Directives/regulations concerning hazardous substances. The information for the user is given in the relevant safety sheet. Empty containers or those containing slight traces of the product must be disposed of in accordance with local regulations. Vermeister S.p.A. guarantees that the details given in this sheet are provided to the best of the company's technical-scientific knowledge and experience; however, the company cannot be held responsible in any way for the results obtained with the products as the conditions of application are beyond the company's control. It is always advisable to check the suitability of the product to each specific circumstance. This sheet cancels and replaces all previous editions.