

## TECHNICAL DATA SHEET

# Ceradura Hardwax-oil

Oil-wax for treating wood floors



3 Lt

COBALT AND KETOXIMES FREE

### DESCRIPTION

Ceradura Hardwax-oil is a particular transparent finishing treatment for wood floors. Ceradura Hardwax-oil is a perfect blend of natural oils and waxes that are carefully balanced to provide the wood with a warm and extremely natural shade, but also offer with high resistance to scratches and stains. The depth of penetration of Ceradura Hardwax-oil guarantees the wood floor has an unbeatable water repellency although it does not alter its normal and essential breathability. The floors treated with Ceradura Hardwax-oil are outstanding for the ease with which they can be maintained and "retouched" in the event of small imperfections in need of repair. The low level odour and the absence of any hazardous additives such as cobalt and ketoxime guarantee that floors treated with Ceradura Hardwax-oil offer a high level of home comfort.

#### TECHNICAL DATA CHEMICAL-PHYSICAL CHARACTERISTICS at 20°C (indicative values not constituting product specifications):

Interval before polishing (min)	5/10
Overcoating (hours)	6/8
Light traffic (hours)	18/24
Careful use (days)	2/3
Completely dry (days)	10/15
Degree of gloss	10
Method of application	Hardwax 8mm roller, brush, pad and Trowel
Average coverage per coat (g/m <sup>2</sup> )	30/50
Stability and storage (in original unopened containers stored in a cool, dry place) months	12
Standard packaging (Lt)	3

### APPLICATION

Sand the floor and fill it with a Vermeister solvent based filler, then prepare the wood support, taking care to use a 120 grit abrasive as the last one. The smoothing and sanding phases must be carried out with particular care because every imperfection will be accentuated by the stain. Clean and vacuum the surface to be treated, then apply Ceradura Hardwax-oil evenly working it in order to avoid the formation of excess product. After about 6/8 hours (harsh environmental conditions and poor ventilation may delay the drying leading to a longer interval), apply another coat of Ceradura Hardwax-oil in the same way.

The treated surfaces are ready for traffic after 2/3 days, but reach their maximum level of protection 10/15 days after application.

Therefore, moderate use of the floors is recommended during the first days following the treatment and the treated surfaces should not be covered with carpets, boxes, sheets,.... etc.

### MAINTENANCE

The maintenance of oiled floors must only be carried out with Soap.Oil, Clean.Oil and Oil.Care and must only begin once the finishing oil is completely hard.

### NOTES

Shake well before use.

OVERCOATING: interval before the application of another coat.

LIGHT TRAFFIC: interval before allowing several people to walk on the floor.

CAREFUL USE: interval before allowing moderate use of the floor.

COMPLETELY HARD: interval before allowing the floor to be used normally: for example by furniture removers, to allow other workmen to carry out their work, starting floor maintenance, etc.

Safety precautions ANY RESIDUE PRODUCT COULD SELF-COMBUST and cloths and tools impregnated with the oil must be soaked in water and, before being disposed of, they must be left to dry in the open air, in areas where there are no risks of flames spreading. Keep the product in a tightly closed, upright container in a cool place away from sources of heat. The product is classified and coded in compliance with EC Directives/regulations concerning hazardous substances. The information for the user is given in the relevant safety sheet. Empty containers or those containing slight traces of the product must be disposed of in accordance with local regulations. Vermeister S.p.A. guarantees that the details given in this sheet are provided to the best of the company's technical-scientific knowledge and experience; however, the company cannot be held responsible in any way for the results obtained with the products as the conditions of application are beyond the company's control. It is always advisable to check the suitability of the product to each specific circumstance. This sheet cancels and replaces all previous editions.