

# DECK.OIL STRONG

High performance protective oil for outdoor use



3 Lt

## DESCRIPTION

A high performance vegetable based protective oil consisting of a balanced blend of various oils designed specifically for outdoor use. DECK.OIL STRONG intensifies the features of softness and warmth while enhancing the grain of the wood.

The main characteristics are:

- greater coverage compared with traditional products;
- excellent shading;
- deep penetration into the wood;
- easy restoration: no sanding required;
- protects against UV rays;
- prevents greying, maintaining the natural colour of the wood;
- protects the wood against water;
- suitable for wood floors and products both indoors and out;
- suitable as a protective coating on floors treated with COLOR.OIL (excluding lighter colours such as white and grey, etc.)

### TECHNICAL DATA CHEMICAL-PHYSICAL CHARACTERISTICS at 20°C (indicative values not constituting product specifications):

Application method	Roller, Brush, Pad
Average coverage per coat (g/m <sup>2</sup> )	40/100
Interval before polishing (minutes)	5/10
Ready for traffic (hours)	16
Stability and storage (in original, unopened containers stored in a cool, dry place) (months)	12
Standard packaging (Lt)	3

## APPLICATION

Prepare the wood, using a 120 grit as the last sanding passage. Apply the product with a roller, brush or cotton pad. For the first coat, especially after a treatment with DECK RESET, and, therefore on rough wood, apply a sufficient quantity (about 70-100 g/sq. m.) to saturate the wood completely until the wood does not absorb any more product. After 5/10 minutes, if required and in the case of an uneven polished/opaque effect, polish the surface with a soft cloth or with a polisher (white or beige pad) to remove any excess product. If necessary, in the case of complete and rapid absorption, to provide the floor with even greater protection, apply a second coat of DECK.OIL STRONG within 3 days, taking care to use a smaller quantity (about 40/50 g/sq. m.) and to remove any excess product using the procedure described above. The duration of this treatment varies greatly according to the location and the intensity of the traffic. In particular, floors exposed to the effects of sea air and intense sunlight will need to have the protective coating restored more frequently. Excessive quantities of product may lead to stickiness and shorter treatment duration.

## MAINTENANCE

The routine maintenance of a floor protected with DECK.OIL consists of three phases:

- dusting with a mop or vacuum cleaner;
- cleaning with SOAP.OIL
- application of Oil.Care for protection

At varying intervals according to the exposure of the floor (approximately every 3-6 months) apply a coat of DECK.OIL STRONG following the method described above. No sanding is required beforehand for maintenance with DECK.OIL STRONG.

The surfaces will be ready for traffic once again after 16 hours.

## NOTES

Shake well before use.

Safety precautions ANY RESIDUE PRODUCT COULD SELF-COMBUST and cloths and tools impregnated with the oil must be soaked in water and, before being disposed of, they must be left to dry in the open air, in areas where there are no risks of flames spreading. Keep the product in a tightly closed, upright container in a cool place away from sources of heat. The product is classified and coded in compliance with EC Directives/regulations concerning hazardous substances. The information for the user is given in the relevant safety sheet. Empty containers or those containing slight traces of the product must be disposed of in accordance with local regulations. VerMeister S.p.A. guarantees that the details given in this sheet are provided to the best of the company's technical-scientific knowledge and experience; however, the company cannot be held responsible in any way for the results obtained with the products as the conditions of application are beyond the company's control. It is always advisable to check the suitability of the product to each specific circumstance. This sheet cancels and replaces all previous editions.