

TECHNICAL DATA SHEET

DECK.CARE

Product for maintaining outdoor wood flooring/oil-treated decks



1 Lt

DESCRIPTION

Emulsion of waxes, natural oils, modified oils and special anti-UV additives, for maintaining outdoor wood flooring/oil-treated decks.

Cobalt-free and MEKO-free (Methyl Ethyl Ketoxime).

DECK.CARE' special oil-wax blend repairs the surface finish that has degraded due to prolonged exposure to atmospheric agents or simply with time, penetrating the wood element and protecting it in-depth, giving the surface a nourished and uniform appearance and creating a water-repellent barrier that prevents water from entering the porosity of the wood.

Does not leave the treated surface slippery.

DECK.CARE is particularly suitable for the protection of any wooden product treated with impregnating products (garden furniture, wooden walls, beams, fences, etc.)

TECHNICAL DATA CHEMICAL-PHYSICAL CHARACTERISTICS at 20°C (indicative values not constituting product specifications):

Application method	Cotton cloth
Dilution in water	20/25%
Recommended frequency	Once every 1-2 months
Walkability (min)	30
Walkability for max performance (hours)	12
Stability and storage (in original unopened containers stored in a cool, dry place)	12 months
Standard packaging (Lt)	1

APPLICATION

Always shake the product before use.

Dilute DECK.CARE with 4-5 parts of clean water. Spread a thin layer evenly using a cotton cloth.

Alternatively, you can spray the diluted product directly on the surface being treated, distributing it evenly, always with the help of a cotton cloth or with a single brush buffer equipped with a white/beige pad.

Do not exceed the quantity of product indicated to avoid the appearance of shiny halos and/or incorrect drying. The treated surfaces will be walkable after 30 minutes, but we strongly recommend applying the treatment when the floor can "rest" for the following 12 hours.

The frequency of maintenance can be regulated as needed. DECK.CARE is usually applied once every 1-2 months, however, depending on traffic or environmental conditions, you may need to apply the product more frequently.

NOTES

Mix well before use.

Incompatible with frost.

Safety precautions. Keep the product in a tightly closed, upright container in a cool place away from sources of heat. The product is classified and coded in compliance with EC Directives/regulations concerning hazardous substances. The information for the user is given in the relevant safety sheet. Empty containers or those containing slight traces of the product must be disposed of in accordance with local regulations. VerMeister S.p.A. guarantees that the details given in this sheet are provided to the best of the company's technical-scientific knowledge and experience; however, the company cannot be held responsible in any way for the results obtained with the products as the conditions of application are beyond the company's control. It is always advisable to check the suitability of the product to each specific circumstance. This sheet cancels and replaces all previous editions.