



TECHNICAL DATA SHEET

ZERO DECK

High performance eco-friendly water oil for outdoor use



5 Lt



DESCRIPTION

High performance eco-friendly water-oil formulated specifically for outdoor use.

ZERO DECK not only brings out the smoothness but also brightens the tone of the wood. Formulated with renewable raw materials and free of heavy metal hardeners, it does not give rise to phenomena of self-combustion like traditional oils.

The main characteristics of the product are:

- low environmental impact
- no hazard labelling
- greater coverage compared with traditional products
- excellent shading
- greater penetration in the wood compared with a solvent based product
- easy to restore: it does not require sanding
- protection against UV rays
- it prevents greying maintaining the colour of the wood over time
- excellent water repellence
- suitable for wood flooring and products both outdoors and indoors.

| TECHNICAL DATA CHEMICAL-PHYSICAL CHARACTERISTICS at 20°C (indicative values not constituting product specifications): | |
|---|--------------------|
| Application method | Roller, Brush, Pad |
| Average coverage per coat (g/m ²) | 50/90 |
| Stability and storage (in original, unopened containers stored in a cool, dry place) (months) | 12 |
| Interval before a 2nd coat, if required (hours) | After 6, within 24 |
| Standard packaging (Lt) | 5 |

APPLICATION

Prepare the wood using a fine 120/150 grain sandpaper last. Apply the product with a roller, brush or cotton pad. For the first coat, especially after a treatment with DECK RESET, and, therefore, on rough wood, apply a quantity that is such as to reach complete saturation (about 50-90 g/sq. m.) (the wood does not absorb any more product and is completely impregnated). After 3/5 minutes, if required and if there is an uneven gloss/matt effect, wipe over the floor manually using a soft cloth to spread and remove any excess product. If necessary, in the case of complete and rapid absorption, to give the floor greater protection, apply after 6 hours and within 1 day, without sanding, a second coat of ZERO DECK, taking care to use a smaller quantity (about 50-60g/sq. m.) and to remove any excess product. The duration of this treatment varies greatly according to the place of exposure and the intensity of the traffic. In particular, floors exposed to the action of sea air and intense sunlight will require more frequent treatments to restore the protective layer.

Excess product could cause an uneven gloss.

MAINTENANCE

The ordinary maintenance of floors protected with ZERO DECK consists of three phases:

- dusting with a mop or a vacuum cleaner;
- washing with SOAP.OIL
- application of the protective DECK CARE

At varying intervals according to the exposure of the floor (approximately every 3-6 months) apply a coat of ZERO DECK following the same methods as those described above.

The surface will be ready for traffic again after 24 hours.

NOTES

Stir well before use.

Safety precautions Keep the product in a tightly closed, upright container in a cool place away from sources of heat. The product is classified and coded in compliance with EC Directives/regulations concerning hazardous substances. The information for the user is given in the relevant safety sheet. Empty containers or those containing slight traces of the product must be disposed of in accordance with local regulations. VerMeister S.p.A. guarantees that the details given in this sheet are provided to the best of the company's technical-scientific knowledge and experience; however, the company cannot be held responsible in any way for the results obtained with the products as the conditions of application are beyond the company's control. It is always advisable to check the suitability of the product to each specific circumstance. This sheet cancels and replaces all previous editions.